



ACCESSORIES

| 6' Powerfeed | 6" Jumper | Splice | L-shaped Connector | T-shaped Connector |
|--------------|---------------|------------|--------------------|--------------------|
| SL-ID-BWBC-6 | SL-ID-W2BC-72 | SL-ID-B2BC | SL-ID-LC | SL-ID-TC |

CONTROLLERS

| | |
|--|--|
| 0/1 ~ 10V Dimming Controller | CNTRL-0-10V-DIM |
| Rotating CCT Scene Remote White / Black | <ul style="list-style-type: none"> • CNTRL-4Z-CCT-RWP-WH • CNTRL-4Z-CCT-RWP-BK |
| 4 Zone CCT Remote | CNTRL-4Z-CCT-RM |

DRIVERS

| Dimmable | |
|--|--|
| Dimmable Electronic LED Driver: | <ul style="list-style-type: none"> • TRE24L40DC • TRE24L96DC |
| Switchex | SX-24V-DD-100W |
| Non-Dimmable | |
| Plug-in Driver | <ul style="list-style-type: none"> • PGID2448 • PGID2496 |
| Indoor/Outdoor driver | LEDDR-24-120W |

Specifications

| | | | |
|-------------------|---------------------------|--------------------------|----------------|
| Input Voltage | 24V DC | Binning | 1BIN |
| Power Consumption | 1.46W/ft (4.8 W/m) | SDCM | <3 |
| Efficacy | 110Lm/w | Lifespan | 50,000 Hours |
| Color Temperature | 3000K | Dimensions (Inches) | .31" W |
| Lumen Output | 160Lm/ft (528Lm/m) | Dimensions (Millimeters) | 8mm W |
| Beam Angle | 140° | Max Length | 40Ft (12M) |
| Dimmable | Yes (PWM / 0-10V / 1-10V) | Custom Cuttable | 2.19" (55.5mm) |
| Chip Type | 2219 | IP Rating | IP40 |
| CRI | 90 | Approved Location | Indoor |
| # per meter | 288 | Warranty | 5 Years |

Ordering Code(s)

- SL-ID-30K-LP-XX-A8 [XX: Length in feet; A: 2219 LED; 8: 8mm PCB]
Available in 20 or 100 feet; For 20 feet: SL-ID-30K-LP-20-A8; For 100 feet: SL-ID-30K-LP-100-A8

| | | | |
|---------|--|---------|--|
| Project | | Type | |
| Date | | Contact | |
| Notes | | | |